

Tip ćelije	Tip ćelije	Kapacitet ćelije 5h	Kapacitet ploče	Dimenzije					
				D	Š	V			
				(mm)	(mm)	V/Vmax (mm)			
(DIN)	(JP)	(Ah)	(Ah)						
2PzS120L	2P250L	120	60	198	47	340./365			
3PzS180L	3P250L	180			65				
4PzS240L	4P250L	240			83				
5PzS300L	5P250L	300			101				
6PzS360L	6P250L	360			119				
7PzS420L	7P250L	420			137				
8PzS480L	8P250L	480			155				
2PzS160L	2P310L	160			80		198	47	405./430
3PzS240L	3P310L	240	65						
4PzS320L	4P310L	320	83						
5PzS400L	5P310L	400	101						
6PzS480L	6P310L	480	119						
7PzS560L	7P310L	560	137						
8PzS640L	8P310L	640	155						
2PzS180L	2P380L	180	90	198		47		475./500	
3PzS270L	3P380L	270			65				
4PzS360L	4P380L	360			83				
5PzS450L	5P380L	450			101				
6PzS540L	6P380L	540			119				
7PzS630L	7P380L	630			137				
8PzS720L	8P380L	720			155				
2PzS210L	2P400L	210			105	198	47		518./543
3PzS315L	3P400L	315	65						
4PzS420L	4P400L	420	83						
5PzS525L	5P400L	525	101						
6PzS630L	6P400L	630	119						
7PzS735L	7P400L	735	137						
8PzS840L	8P400L	840	155						
2PzS230L	2P440L	230	115	198			47	osnovna visina: 570./595 na zahtev: *** 550./575	
3PzS345L	3P440L	345			65				
4PzS460L	4P440L	460			83				
5PzS575L	5P440L	575			101				
6PzS690L	6P440L	690			119				
7PzS805L	7P440L	805			137				
8PzS920L	8P440L	920			155				
2PzS250L	2P445L	250			125	198	47		570./595
3PzS375L	3P445L	375	65						
4PzS500L	4P445L	500	83						
5PzS625L	5P445L	625	101						
6PzS750L	6P445L	750	119						
7PzS875L	7P445L	875	137						
8PzS1000L	8P445L	1000	155						
3PzS420L	3P550L	420	140	198			65	osnovna visina: 720./745 na zahtev: *** 700./725	
4PzS560L	4P550L	560			83				
5PzS700L	5P550L	700			101				
6PzS840L	6P550L	840			119				
7PzS980L	7P550L	980			137				
8PzS1120L	8P550L	1120			155				
3PzS465L	3P555L	465			155	198	65		720./745
4PzS620L	4P555L	620					83		
5PzS775L	5P555L	775	101						
6PzS930L	6P555L	930	119						
7PzS1085L	7P555L	1085	137						
8PzS1240L	8P555L	1240	155						

FLEKSIBILNA SPOJNICA		
	Dimenzije (mm)	
	35*75	50*130
	35*95	50*150
	35*110	50*170
	35*130	70*95
	35*150	70*110
	35*170	70*130
50*95	70*150	
50*110	70*170	
KABL ZA KONEKTOR		
	35*1500 mm, primena do 540 Ah	
	50*1500 mm, primena od 541Ah do 770 Ah	
	70*1500 mm, primena: od 771 Ah	
ŠRAFOVI KONEKTORSKIH KABLOVA		
	Dimenzije (mm)	
	M10*22 mesingani	
SISTEM ZA GRAVITACIONO DOLIVANJE VODE		
	09KUM1 (Ž) konekcija Nw10	

REZERVNI DELOVI SISTEMA ZA DOLIVANJE VODE U TRAKCIONIM BATERIJAMA	
Čepovi za ćelije	
Plovak	2220
Plovak	2224
Plovak	2229
Plovak	2234
Plovak	2239
Plovak	2244
Plovak	2249
Plovak	2259
Krivina za centralno nalivanje	T 10/6/10
Krivina za centralno nalivanje	T 10/10/10
Krivina za centralno nalivanje	ugao 10/6
PVC crevo za centralno nalivanje	NW6/metara
PVC crevo za centralno nalivanje	NW10/metara
Čep za centralno nalivanje	krajnji deo Nw6
Poklopac za prašinu	"C"
Šelna za crevo za centralno nalivanje	Nw6
Šelna za crevo za centralno nalivanje	Nw10
Konektor za centralno nalivanje (muški)	Nw10
Konektor za centralno nalivanje (ženski)	Nw10
Indikator protoka	
T krivina za centralno nalivanje	T 6/10/6
T krivina za centralno nalivanje	T 6/6/6
Razdelnik centralnog nalivanja	6/10/6/10
Razdelnik centralnog nalivanja	6/6/6/6
Kertridž za prečišćavanje vode	



Uvoznik i distributer:
EXXOL d.o.o.
 18252 Merošina-Niš, Srbija,
 Telefon/Fax: 018 285 555
 www.exxol.com; e-mail: info@exxol.rs

Distributer:
EXOL-STARTER d.o.o.
 ul. Igora Vasiljeva 33n, 11000 Beograd
 Telefon/Fax: 011 2710 471
 e-mail: info@exol-starter.com